NAME

getopt − get option letter from argv

SYNOPSIS

int getopt(argc, argv, optstring)
int argc;
char **argv;
char *optstring;

extern char *optarg;
extern int optind;

DESCRIPTION

Getopt returns the next option letter in *argv* that matches a letter in *optstring*. *Optstring* is a string of recognized option letters; if a letter is followed by a colon, the option is expected to have an argument that may or may not be separated from it by white space. *Optarg* is set to point to the start of the option argument on return from *getopt*.

Getopt places in *optind* the *argv* index of the next argument to be processed. Because *optind* is external, it is normally initialized to zero automatically before the first call to *getopt*.

When all options have been processed (i.e., up to the first non-option argument), *getopt* returns **EOF**. The special option −− may be used to delimit the end of the options; **EOF** will be returned, and −− will be skipped.

DIAGNOSTICS

Getopt prints an error message on *stderr* and returns a question mark (**?**) when it encounters an option letter not included in *optstring*.

EXAMPLE

The following code fragment shows how one might process the arguments for a command that can take the mutually exclusive options **a** and **b**, and the options **f** and **o**, both of which require arguments:

```
main(argc, argv)
int argc;
char **argv;
{
        int c;
        extern int optind;
        extern char *optarg;
        .
        .
        .
        while ((c = getopt(argc, argv, "abf:o:")) != EOF)
                switch (c) {
                case ‘a’:
                        if (bflg)
                                errflg++;
                        else
                                aflg++;
                        break;
                case ‘b’:
                        if (aflg)
                                errflg++;
                        else
                                bproc();
                        break;
                case ‘f’:
                        ifile = optarg;
                        break;
```

```
                        case ‘o’:
                                ofile = optarg;
                                break;
                        case ‘?’:
                        default:
                                errflg++;
                                break;
                        }
                if (errflg) {
                        fprintf(stderr, "Usage: ...");
                        exit(2);
                }
                for (; optind < argc; optind++) {
                        .
                        .
                        .
                }
                .
                .
                .
}
```

HISTORY

Written by Henry Spencer, working from a Bell Labs manual page. Modified by Keith Bostic to behave more like the System V version.

BUGS

It is not obvious how ‘−’ standing alone should be treated; this version treats it as a non-option argument, which is not always right.

Option arguments are allowed to begin with ‘−’; this is reasonable but reduces the amount of error checking possible.

Getopt is quite flexible but the obvious price must be paid: there is much it could do that it doesn’t, like checking mutually exclusive options, checking type of option arguments, etc.